

Section 3705(c) requires existing crude oil tankers of 20,000 deadweight tons or above, but less than 40,000 deadweight tons, that are 15 years or older, to have segregated ballast tanks or a crude oil washing system by January 1, 1985 or if less than 15 years old, by the date on which it reaches 15 years of age.

Section 3705(d) requires existing crude oil tankers of 20,000 deadweight tons or above, to install an inert gas system. An exemption for crude oil tankers of less than 40,000 deadweight tons not fitted with high-capacity tank washing machines may be granted by the Secretary, only if it is demonstrated that compliance would be unreasonable and impracticable due to the vessel's design characteristics.

Section 3705(e) requires existing crude oil tankers of 20,000 deadweight tons or above, engaged in the transfer of oil from Outer Continental Shelf oil exploitation or production facilities, to have segregated ballast tanks or be operated with dedicated clean ballast tanks or special ballast arrangements.

**§ 3706. Product carrier minimum standards**

(a) A new product carrier of at least 30,000 deadweight tons shall be equipped with protectively located segregated ballast tanks.

(b) A new product carrier of at least 20,000 deadweight tons shall be equipped with a cargo tank protection system consisting of a fixed deck froth system and a fixed inert gas system or, if the product carrier carries dedicated products incompatible with the cargo tank protection system, an alternate protection system authorized by the Secretary.

(c) An existing product carrier of at least 40,000 deadweight tons shall be equipped with segregated ballast tanks or may operate with dedicated clean ballast tanks.

(d) An existing product carrier of at least 20,000 deadweight tons but less than 40,000 deadweight tons, and at least 15 years of age, shall be equipped with segregated ballast tanks or may operate with dedicated clean ballast tanks before January 2, 1986, or the date on which it reaches 15 years of age, whichever is later.

(e) An existing product carrier of at least 40,000 deadweight tons, or an existing product carrier of at least 20,000 deadweight tons but less than 40,000 deadweight tons that is fitted with high-capacity tank washing machines, shall be equipped with an inert gas system.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 523.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3706(a) .....	46:391a(7)(B)
3706(b) .....	46:391a(7)(C)
3706(c) .....	46:391a(7)(G)
3706(d) .....	46:391a(7)(H)
3706(e) .....	46:391a(7)(I)

Section 3706 requires compliance with certain minimum standards by a product carrier, which is a self-propelled tank vessel.

Section 3706(a) requires new product carriers of 30,000 deadweight tons or above, to have protectively located segregated ballast tanks.

Section 3706(b) requires new product carriers of 20,000 deadweight tons or above, to have a cargo tank protection system consisting of a fixed deck froth system or a fixed inert gas system. If the products carried are incompatible with the cargo tank protection system, then an alternative protection system may be authorized.

Section 3706(c) requires existing product carriers of 40,000 deadweight tons or above, to have segregated bal-

last tanks or to operate with dedicated clean ballast tanks.

Section 3706(d) requires existing product carriers of 20,000 deadweight tons or above, but less than 40,000 deadweight tons, that are 15 years or older, to have segregated ballast tanks by January 1, 1985, or on the date on which it reaches 15 years of age or, in the alternative, that the vessel operate with dedicated clean ballast tanks.

Section 3706(e) requires existing product carriers of 40,000 deadweight tons or above, or to existing product carriers, fitted with high-capacity tank washing machines, of 20,000 deadweight tons but less than 40,000 deadweight tons, to install an inert gas system.

**§ 3707. Tanker minimum standards**

(a) A new tanker of at least 10,000 gross tons as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title shall be equipped with—

(1) 2 remote steering gear control systems operable separately from the navigating bridge;

(2) the main steering gear control in the steering gear compartment;

(3) means of communications and rudder angle indicators on the navigating bridge, a remote steering gear control station, and the steering gear compartment;

(4) at least 2 identical and adequate power units for the main steering gear;

(5) an alternative and adequate power supply, either from an emergency source of electrical power or from another independent source of power located in the steering gear compartment; and

(6) means of automatic starting and stopping of power units with attendant alarms at all steering stations.

(b) An existing tanker of at least 10,000 gross tons as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title shall be equipped with—

(1) 2 remote steering gear control systems operable separately from the navigating bridge;

(2) the main steering gear control in the steering gear compartment; and

(3) means of communications and rudder angle indicators on the navigating bridge, a remote steering gear control station, and the steering gear compartment.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524; Pub. L. 104-324, title VII, §716, Oct. 19, 1996, 110 Stat. 3937.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3707(a) .....	46:391a(7)(K)
3707(b) .....	46:391a(7)(L)

Section 3707 requires compliance with certain minimum standards by a tanker, which is a self-propelled tank vessel.

Section 3707(a) requires new tankers of 10,000 gross tons or above, to have two remote steering gear control systems, a main steering gear control in the steering gear compartment, a means of communications and

rudder angle indicators at specified locations, two or more specified power units for the main steering gear, an alternative and adequate power supply of specified characteristics, and a means of automatic operation of power units, with attendant alarms at all steering stations.

Section 3707(b) requires existing tankers of 10,000 gross tons or above, to have two remote steering gear control systems, a main steering gear control in the steering gear compartment, and a means of communication and rudder angle indicators at specified locations.

AMENDMENTS

1996—Subsec. (a). Pub. L. 104-324, §716(1), inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons” in introductory provisions.

Subsec. (b). Pub. L. 104-324, §716(2), inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons”.

§ 3708. Self-propelled tank vessel minimum standards

A self-propelled tank vessel of at least 10,000 gross tons as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title shall be equipped with—

- (1) a dual radar system with short-range and long-range capabilities, each with true-north features;
(2) an electronic relative motion analyzer that is at least functionally equivalent to equipment complying with specifications established by the Secretary of Transportation;
(3) an electronic position-fixing device;
(4) adequate communications equipment;
(5) a sonic depth finder;
(6) a gyrocompass; and
(7) up-to-date charts.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524; Pub. L. 104-324, title VII, §717, Oct. 19, 1996, 110 Stat. 3937.)

HISTORICAL AND REVISION NOTES

Table with 2 columns: Revised section, Source section (U.S. Code). Row 1: 3708 ..... 46:391a(7)(J)

Section 3708 requires compliance with certain minimum standards by a self-propelled tank vessel. These requirements apply to any tank vessel of 10,000 gross tons or above with no distinction being made as to whether or not the vessel is “primarily” constructed or adapted to carry oil or hazardous material in bulk in the cargo spaces. These vessels are required to be equipped with a dual radar system, a computerized relative motion analyzer, an electronic position fixing device, adequate communications equipment, a sonic depth finder, a gyrocompass, and up-to-date charts.

AMENDMENTS

1996—Pub. L. 104-324 inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons”.

§ 3709. Exemptions

The Secretary may exempt a vessel from the minimum requirements established by sections

3704-3706 of this title for segregated ballast, crude oil washing, and dedicated clean ballast if the Secretary decides that shore-based reception facilities are a preferred method of handling ballast and that adequate facilities are readily available.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524.)

HISTORICAL AND REVISION NOTES

Table with 2 columns: Revised section, Source section (U.S. Code). Row 1: 3709 ..... 46:391a(7)(N)

Section 3709 provides the Secretary with the authority to exempt certain minimum tanker requirements of sections 3704, 3705, and 3706 when shorebased reception facilities are a better way of handling ballast and when the facilities are adequate and readily available.

§ 3710. Evidence of compliance by vessels of the United States

(a) A vessel of the United States to which this chapter applies that has on board oil or hazardous material in bulk as cargo or cargo residue must have a certificate of inspection issued under this part, endorsed to indicate that the vessel complies with regulations prescribed under this chapter.

(b) Each certificate endorsed under this section is valid for not more than 5 years and may be renewed as specified by the Secretary. In appropriate circumstances, the Secretary may issue a temporary certificate valid for not more than 30 days. A certificate shall be suspended or revoked if the Secretary finds that the vessel does not comply with the conditions under which the certificate was issued.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524; Pub. L. 104-324, title VI, §605(b), Oct. 19, 1996, 110 Stat. 3931.)

HISTORICAL AND REVISION NOTES

Table with 2 columns: Revised section, Source section (U.S. Code). Row 1: 3710 ..... 46:391a(8)(A), 46:391a(8)(E)

Section 3710 prohibits any vessels of the United States subject to this chapter from having on board oil or hazardous material in bulk as cargo or in residue, unless it has a required Certificate of Inspection endorsed to indicate vessel compliance with applicable regulations. Certificates shall be valid for a period not to exceed two years and may be renewed as specified by the Secretary. The Secretary may issue temporary certificates of not more than thirty days duration and may revoke or suspend any certificate under designated circumstances.

AMENDMENTS

1996—Subsec. (b). Pub. L. 104-324 substituted “5 years” for “24 months”.

§ 3711. Evidence of compliance by foreign vessels

(a) A foreign vessel to which this chapter applies may operate on the navigable waters of the United States, or transfer oil or hazardous material in a port or place under the jurisdiction of the United States, only if the vessel has been issued a certificate of compliance by the Secretary. The Secretary may issue the certificate only after the vessel has been examined and found to be in compliance with this chapter and