

deadweight tons, that are 15 years or older, to have segregated ballast tanks by January 1, 1985, or on the date on which it reaches 15 years of age or, in the alternative, that the vessel operate with dedicated clean ballast tanks.

Section 3706(e) requires existing product carriers of 40,000 deadweight tons or above, or to existing product carriers, fitted with high-capacity tank washing machines, of 20,000 deadweight tons but less than 40,000 deadweight tons, to install an inert gas system.

§ 3707. Tanker minimum standards

(a) A new tanker of at least 10,000 gross tons as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title shall be equipped with—

- (1) 2 remote steering gear control systems operable separately from the navigating bridge;
- (2) the main steering gear control in the steering gear compartment;
- (3) means of communications and rudder angle indicators on the navigating bridge, a remote steering gear control station, and the steering gear compartment;
- (4) at least 2 identical and adequate power units for the main steering gear;
- (5) an alternative and adequate power supply, either from an emergency source of electrical power or from another independent source of power located in the steering gear compartment; and
- (6) means of automatic starting and stopping of power units with attendant alarms at all steering stations.

(b) An existing tanker of at least 10,000 gross tons as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title shall be equipped with—

- (1) 2 remote steering gear control systems operable separately from the navigating bridge;
- (2) the main steering gear control in the steering gear compartment; and
- (3) means of communications and rudder angle indicators on the navigating bridge, a remote steering gear control station, and the steering gear compartment.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524; Pub. L. 104-324, title VII, § 716, Oct. 19, 1996, 110 Stat. 3937.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3707(a)	46:391a(7)(K)
3707(b)	46:391a(7)(L)

Section 3707 requires compliance with certain minimum standards by a tanker, which is a self-propelled tank vessel.

Section 3707(a) requires new tankers of 10,000 gross tons or above, to have two remote steering gear control systems, a main steering gear control in the steering gear compartment, a means of communications and rudder angle indicators at specified locations, two or more specified power units for the main steering gear, an alternative and adequate power supply of specified characteristics, and a means of automatic operation of

power units, with attendant alarms at all steering stations.

Section 3707(b) requires existing tankers of 10,000 gross tons or above, to have two remote steering gear control systems, a main steering gear control in the steering gear compartment, and a means of communication and rudder angle indicators at specified locations.

AMENDMENTS

1996—Subsec. (a). Pub. L. 104-324, § 716(1), inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons” in introductory provisions.

Subsec. (b). Pub. L. 104-324, § 716(2), inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons”.

§ 3708. Self-propelled tank vessel minimum standards

A self-propelled tank vessel of at least 10,000 gross tons as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title shall be equipped with—

- (1) a dual radar system with short-range and long-range capabilities, each with true-north features;
- (2) an electronic relative motion analyzer that is at least functionally equivalent to equipment complying with specifications established by the Secretary of Transportation;
- (3) an electronic position-fixing device;
- (4) adequate communications equipment;
- (5) a sonic depth finder;
- (6) a gyrocompass; and
- (7) up-to-date charts.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524; Pub. L. 104-324, title VII, § 717, Oct. 19, 1996, 110 Stat. 3937.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3708	46:391a(7)(J)

Section 3708 requires compliance with certain minimum standards by a self-propelled tank vessel. These requirements apply to any tank vessel of 10,000 gross tons or above with no distinction being made as to whether or not the vessel is “primarily” constructed or adapted to carry oil or hazardous material in bulk in the cargo spaces. These vessels are required to be equipped with a dual radar system, a computerized relative motion analyzer, an electronic position fixing device, adequate communications equipment, a sonic depth finder, a gyrocompass, and up-to-date charts.

AMENDMENTS

1996—Pub. L. 104-324 inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons”.

§ 3709. Exemptions

The Secretary may exempt a vessel from the minimum requirements established by sections 3704-3706 of this title for segregated ballast,

crude oil washing, and dedicated clean ballast if the Secretary decides that shore-based reception facilities are a preferred method of handling ballast and that adequate facilities are readily available.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3709	46:391a(7)(N)

Section 3709 provides the Secretary with the authority to exempt certain minimum tanker requirements of sections 3704, 3705, and 3706 when shorebased reception facilities are a better way of handling ballast and when the facilities are adequate and readily available.

§ 3710. Evidence of compliance by vessels of the United States

(a) A vessel of the United States to which this chapter applies that has on board oil or hazardous material in bulk as cargo or cargo residue must have a certificate of inspection issued under this part, endorsed to indicate that the vessel complies with regulations prescribed under this chapter.

(b) Each certificate endorsed under this section is valid for not more than 5 years and may be renewed as specified by the Secretary. In appropriate circumstances, the Secretary may issue a temporary certificate valid for not more than 30 days. A certificate shall be suspended or revoked if the Secretary finds that the vessel does not comply with the conditions under which the certificate was issued.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524; Pub. L. 104-324, title VI, §605(b), Oct. 19, 1996, 110 Stat. 3931.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3710	46:391a(8)(A) 46:391a(8)(E)

Section 3710 prohibits any vessels of the United States subject to this chapter from having on board oil or hazardous material in bulk as cargo or in residue, unless it has a required Certificate of Inspection endorsed to indicate vessel compliance with applicable regulations. Certificates shall be valid for a period not to exceed two years and may be renewed as specified by the Secretary. The Secretary may issue temporary certificates of not more than thirty days duration and may revoke or suspend any certificate under designated circumstances.

AMENDMENTS

1996—Subsec. (b). Pub. L. 104-324 substituted “5 years” for “24 months”.

§ 3711. Evidence of compliance by foreign vessels

(a) A foreign vessel to which this chapter applies may operate on the navigable waters of the United States, or transfer oil or hazardous material in a port or place under the jurisdiction of the United States, only if the vessel has been issued a certificate of compliance by the Secretary. The Secretary may issue the certificate only after the vessel has been examined and found to be in compliance with this chapter and regulations prescribed under this chapter. The

Secretary may accept any part of a certificate, endorsement, or document, issued by the government of a foreign country under a treaty, convention, or other international agreement to which the United States is a party, as a basis for issuing a certificate of compliance.

(b) A certificate issued under this section is valid for not more than 24 months and may be renewed as specified by the Secretary. In appropriate circumstances, the Secretary may issue a temporary certificate valid for not more than 30 days.

(c) A certificate shall be suspended or revoked if the Secretary finds that the vessel does not comply with the conditions under which the certificate was issued.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 525.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3711	46:391a(8)(B) 46:391a(8)(C) 46:391a(8)(E)

Section 3711 prohibits any foreign vessel from operating on the navigable waters of the United States or from transferring oil or hazardous material in any port or place under the jurisdiction of the United States, unless it has a certificate of compliance issued by the Secretary indicating that the vessel has been examined and found to be in compliance with the provisions of the applicable regulations. It also authorizes the Secretary to accept, in whole or in part, an appropriate foreign certificate issued pursuant to any international agreement to which the United States is a party, as a basis for issuing the certificate of compliance. This means that the Secretary does not have to accept foreign certificates as evidence of compliance, but may take additional action to assure compliance with applicable domestic laws and regulations and international treaty provisions.

§ 3712. Notification of noncompliance

The Secretary shall notify the owner, charterer, managing operator, agent, master, or individual in charge of a vessel found not to be in compliance with a regulation prescribed under this part and state how compliance may be achieved.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 525.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3712	46:391a(8)(A) 46:391a(8)(B)

Section 3712 requires the Secretary to notify appropriate parties when a vessel is found not to be in compliance with applicable requirements, standards, or regulations and what remedial steps must be taken in order to comply with them.

§ 3713. Prohibited acts

(a) A person may not—

(1) violate this chapter or a regulation prescribed under this chapter;

(2) refuse to permit any official, authorized by the Secretary to enforce this chapter, to board a vessel or to enter a shore area, place, or premises, under a person’s control to make an inspection under this chapter; or

(3) refuse to obey a lawful directive issued under this chapter.