

been certified to meet for any model year the clean-fuel vehicle standards applicable under this part for that model year to clean-fuel vehicles in that class or category.

(July 14, 1955, ch. 360, title II, § 241, as added Pub. L. 101-549, title II, § 229(a), Nov. 15, 1990, 104 Stat. 2511.)

§ 7582. Requirements applicable to clean-fuel vehicles

(a) Promulgation of standards

Not later than 24 months after November 15, 1990, the Administrator shall promulgate regulations under this part containing clean-fuel vehicle standards for the clean-fuel vehicles specified in this part.

(b) Other requirements

Clean-fuel vehicles of up to 8,500 gvwr subject to standards set forth in this part shall comply with all motor vehicle requirements of this subchapter (such as requirements relating to on-board diagnostics, evaporative emissions, etc.) which are applicable to conventional gasoline-fueled vehicles of the same category and model year, except as provided in section 7584 of this title with respect to administration and enforcement, and except to the extent that any such requirement is in conflict with the provisions of this part. Clean-fuel vehicles of 8,500 gvwr or greater subject to standards set forth in this part shall comply with all requirements of this subchapter which are applicable in the case of conventional gasoline-fueled or diesel fueled vehicles of the same category and model year, except as provided in section 7584 of this title with respect to administration and enforcement, and except to the extent that any such requirement is in conflict with the provisions of this part.

(c) In-use useful life and testing

(1) In the case of light-duty vehicles and light-duty trucks up to 6,000 lbs gvwr, the useful life for purposes of determining in-use compliance with the standards under section 7583 of this title shall be—

(A) a period of 5 years or 50,000 miles (or the equivalent) whichever first occurs, in the case of standards applicable for purposes of certification at 50,000 miles; and

(B) a period of 10 years or 100,000 miles (or the equivalent) whichever first occurs, in the case of standards applicable for purposes of certification at 100,000 miles, except that in-use testing shall not be done for a period beyond 7 years or 75,000 miles (or the equivalent) whichever first occurs.

(2) In the case of light-duty trucks of more than 6,000 lbs gvwr, the useful life for purposes of determining in-use compliance with the standards under section 7583 of this title shall be—

(A) a period of 5 years or 50,000 miles (or the equivalent) whichever first occurs in the case of standards applicable for purposes of certification at 50,000 miles; and

(B) a period of 11 years or 120,000 miles (or the equivalent) whichever first occurs in the case of standards applicable for purposes of certification at 120,000 miles, except that in-

use testing shall not be done for a period beyond 7 years or 90,000 miles (or the equivalent) whichever first occurs.

(July 14, 1955, ch. 360, title II, § 242, as added Pub. L. 101-549, title II, § 229(a), Nov. 15, 1990, 104 Stat. 2513.)

§ 7583. Standards for light-duty clean-fuel vehicles

(a) Exhaust standards for light-duty vehicles and certain light-duty trucks

The standards set forth in this subsection shall apply in the case of clean-fuel vehicles which are light-duty trucks of up to 6,000 lbs. gross vehicle weight rating (gvwr) (but not including light-duty trucks of more than 3,750 lbs. loaded vehicle weight (lvw)) or light-duty vehicles:

(1) Phase I

Beginning with model year 1996, for the air pollutants specified in the following table, the clean-fuel vehicle standards under this section shall provide that vehicle exhaust emissions shall not exceed the levels specified in the following table:

PHASE I CLEAN FUEL VEHICLE EMISSION STANDARDS FOR LIGHT-DUTY TRUCKS OF UP TO 3,750 LBS. LVW AND UP TO 6,000 LBS. GVWR AND LIGHT-DUTY VEHICLES

Pollutant	NMOG	CO	NO _x	PM	HCHO (formaldehyde)
50,000 mile standard.	0.125	3.4	0.4	0.015
100,000 mile standard.	0.156	4.2	0.6	0.08*	0.018

Standards are expressed in grams per mile (gpm).

*Standards for particulates (PM) shall apply only to diesel-fueled vehicles.

In the case of the 50,000 mile standards and the 100,000 mile standards, for purposes of certification, the applicable useful life shall be 50,000 miles or 100,000 miles, respectively.

(2) Phase II

Beginning with model year 2001, for air pollutants specified in the following table, the clean-fuel vehicle standards under this section shall provide that vehicle exhaust emissions shall not exceed the levels specified in the following table.

PHASE II CLEAN FUEL VEHICLE EMISSION STANDARDS FOR LIGHT-DUTY TRUCKS OF UP TO 3,750 LBS. LVW AND UP TO 6,000 LBS. GVWR AND LIGHT-DUTY VEHICLES

Pollutant	NMOG	CO	NO _x	PM*	HCHO (formaldehyde)
50,000 mile standard.	0.075	3.4	0.2	0.015
100,000 mile standard.	0.090	4.2	0.3	0.08	0.018

Standards are expressed in grams per mile (gpm).

*Standards for particulates (PM) shall apply only to diesel-fueled vehicles.

In the case of the 50,000 mile standards and the 100,000 mile standards, for purposes of certification, the applicable useful life shall be 50,000 miles or 100,000 miles, respectively.