the records of the owner or operator are insufficient to confirm the established maximum allowable operating pressure of the segment.

(2) EXCEEDANCES OF MAXIMUM ALLOWABLE OP-ERATING PRESSURE.—If there is an exceedance of the maximum allowable operating pressure with respect to a gas transmission pipeline of an owner or operator of a pipeline facility that exceeds the build-up allowed for operation of pressure-limiting or control devices, the owner or operator shall report the exceedance to the Secretary and appropriate State authorities on or before the 5th day following the date on which the exceedance occurs.

(c) DETERMINATION OF MAXIMUM ALLOWABLE OPERATING PRESSURE.—

(1) IN GENERAL.—In the case of a transmission line of an owner or operator of a pipeline facility identified under subsection (b)(1), the Secretary shall—

(A) require the owner or operator to reconfirm a maximum allowable operating pressure as expeditiously as economically feasible; and

(B) determine what actions are appropriate for the pipeline owner or operator to take to maintain safety until a maximum allowable operating pressure is confirmed.

(2) INTERIM ACTIONS.—In determining the actions for an owner or operator of a pipeline facility to take under paragraph (1)(B), the Secretary shall take into account potential consequences to public safety and the environment, potential impacts on pipeline system reliability and deliverability, and other factors, as appropriate.

(d) TESTING REGULATIONS.-

(1) IN GENERAL.—Not later than 18 months after the date of enactment of this section, the Secretary shall issue regulations for conducting tests to confirm the material strength of previously untested natural gas transmission pipelines located in high-consequence areas and operating at a pressure greater than 30 percent of specified minimum yield strength.

(2) CONSIDERATIONS.—In developing the regulations, the Secretary shall consider safety testing methodologies, including, at a minimum—

(A) pressure testing; and

(B) other alternative methods, including in-line inspections, determined by the Secretary to be of equal or greater effectiveness.

(3) COMPLETION OF TESTING.—The Secretary, in consultation with the Chairman of the Federal Energy Regulatory Commission and State regulators, as appropriate, shall establish timeframes for the completion of such testing that take into account potential consequences to public safety and the environment and that minimize costs and service disruptions.

(e) HIGH-CONSEQUENCE AREA DEFINED.—In this section, the term "high-consequence area" means an area described in section 60109(a).

(Added Pub. L. 112-90, §23(a), Jan. 3, 2012, 125 Stat. 1918.)

References in Text

The date of enactment of this section, referred to in subsecs. (a)(1), (b)(1), and (d)(1), is the date of enactment of Pub. L. 112-90, which was approved Jan. 3, 2012.

§60140. Cover over buried pipelines

(a) HAZARDOUS LIQUID PIPELINE INCIDENTS IN-VOLVING BURIED PIPELINES.—

(1) STUDY.—The Secretary of Transportation shall conduct a study of hazardous liquid pipeline incidents at crossings of inland bodies of water with a width of at least 100 feet from high water mark to high water mark to determine if the depth of cover over the buried pipeline was a factor in any accidental release of hazardous liquids.

(2) REPORT.—Not later than 1 year after the date of enactment of this section, the Secretary shall transmit to the Committee on Transportation and Infrastructure and the Committee on Energy and Commerce of the House of Representatives and the Committee on Commerce, Science, and Transportation of the Senate a report on the results of the study.

(b) Assessment of Current Requirements for Depth of Cover Over Buried Pipelines.—

(1) IN GENERAL.—If, following completion of the study under subsection (a), the Secretary finds that the depth of cover over buried pipelines is a contributing factor in the accidental release of hazardous liquids from the pipelines, the Secretary, not later than 1 year after the date of completion of the study, shall review and determine the sufficiency of current requirements for the depth of cover over buried pipelines.

(2) LEGISLATIVE RECOMMENDATIONS.—

(A) DEVELOPMENT.—If the Secretary determines under paragraph (1) that the current requirements for the depth of cover over buried pipelines are insufficient, the Secretary shall develop legislative recommendations for improving the safety of buried pipelines at crossings of inland bodies of water with a width of at least 100 feet from high water mark to high water mark.

(B) CONSIDERATION OF FACTORS.—In developing legislative recommendations under subparagraph (A), the Secretary shall consider the factors specified in section 60102(b)(2).

(C) REPORT TO CONGRESS.—If the Secretary develops legislative recommendations under subparagraph (A), the Secretary shall submit to the committees referred to in subsection (a)(2) a report containing the legislative recommendations.

(Added Pub. L. 112–90, §28(a), Jan. 3, 2012, 125 Stat. 1920.)

References in Text

The date of enactment of this section, referred to in subsec. (a)(2), is the date of enactment of Pub. L. 112-90, which was approved Jan. 3, 2012.

§60141. Standards for underground natural gas storage facilities

(a) MINIMUM SAFETY STANDARDS.—Not later than 2 years after the date of enactment of the