

Section 3707 requires compliance with certain minimum standards by a tanker, which is a self-propelled tank vessel.

Section 3707(a) requires new tankers of 10,000 gross tons or above, to have two remote steering gear control systems, a main steering gear control in the steering gear compartment, a means of communications and rudder angle indicators at specified locations, two or more specified power units for the main steering gear, an alternative and adequate power supply of specified characteristics, and a means of automatic operation of power units, with attendant alarms at all steering stations.

Section 3707(b) requires existing tankers of 10,000 gross tons or above, to have two remote steering gear control systems, a main steering gear control in the steering gear compartment, and a means of communication and rudder angle indicators at specified locations.

**Editorial Notes**

AMENDMENTS

1996—Subsec. (a). Pub. L. 104-324, §716(1), inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons” in introductory provisions.

Subsec. (b). Pub. L. 104-324, §716(2), inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons”.

**§ 3708. Self-propelled tank vessel minimum standards**

A self-propelled tank vessel of at least 10,000 gross tons as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title shall be equipped with—

- (1) a dual radar system with short-range and long-range capabilities, each with true-north features;
- (2) an electronic relative motion analyzer that is at least functionally equivalent to equipment complying with specifications established by the Secretary of Transportation;
- (3) an electronic position-fixing device;
- (4) adequate communications equipment;
- (5) a sonic depth finder;
- (6) a gyrocompass; and
- (7) up-to-date charts.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524; Pub. L. 104-324, title VII, §717, Oct. 19, 1996, 110 Stat. 3937.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3708 .....	46:391a(7)(J)

Section 3708 requires compliance with certain minimum standards by a self-propelled tank vessel. These requirements apply to any tank vessel of 10,000 gross tons or above with no distinction being made as to whether or not the vessel is “primarily” constructed or adapted to carry oil or hazardous material in bulk in the cargo spaces. These vessels are required to be equipped with a dual radar system, a computerized relative motion analyzer, an electronic position fixing device, adequate communications equipment, a sonic depth finder, a gyrocompass, and up-to-date charts.

**Editorial Notes**

AMENDMENTS

1996—Pub. L. 104-324 inserted “as measured under section 14502 of this title, or an alternate tonnage measured under section 14302 of this title as prescribed by the Secretary under section 14104 of this title” after “10,000 gross tons”.

**§ 3709. Exemptions**

The Secretary may exempt a vessel from the minimum requirements established by sections 3704-3706 of this title for segregated ballast, crude oil washing, and dedicated clean ballast if the Secretary decides that shore-based reception facilities are a preferred method of handling ballast and that adequate facilities are readily available.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3709 .....	46:391a(7)(N)

Section 3709 provides the Secretary with the authority to exempt certain minimum tanker requirements of sections 3704, 3705, and 3706 when shorebased reception facilities are a better way of handling ballast and when the facilities are adequate and readily available.

**§ 3710. Evidence of compliance by vessels of the United States**

(a) A vessel of the United States to which this chapter applies that has on board oil or hazardous material in bulk as cargo or cargo residue must have a certificate of inspection issued under this part, endorsed to indicate that the vessel complies with regulations prescribed under this chapter.

(b) Each certificate endorsed under this section is valid for not more than 5 years and may be renewed as specified by the Secretary. In appropriate circumstances, the Secretary may issue a temporary certificate valid for not more than 30 days. A certificate shall be suspended or revoked if the Secretary finds that the vessel does not comply with the conditions under which the certificate was issued.

(Pub. L. 98-89, Aug. 26, 1983, 97 Stat. 524; Pub. L. 104-324, title VI, §605(b), Oct. 19, 1996, 110 Stat. 3931.)

HISTORICAL AND REVISION NOTES

<i>Revised section</i>	<i>Source section (U.S. Code)</i>
3710 .....	46:391a(8)(A) 46:391a(8)(E)

Section 3710 prohibits any vessels of the United States subject to this chapter from having on board oil or hazardous material in bulk as cargo or in residue, unless it has a required Certificate of Inspection endorsed to indicate vessel compliance with applicable regulations. Certificates shall be valid for a period not to exceed two years and may be renewed as specified by the Secretary. The Secretary may issue temporary certificates of not more than thirty days duration and may revoke or suspend any certificate under designated circumstances.