

sible shot firing units. Only incombustible materials shall be used for stemming boreholes. The Secretary may, under such safeguards as he may prescribe, permit the firing of more than twenty shots and allow the use of nonpermissible explosives in sinking shafts and slopes from the surface in rock. Nothing in this section shall prohibit the use of compressed air blasting.

(d) Container construction for carrying explosives or detonators in underground mines

Explosives or detonators carried anywhere underground in a coal mine by any person shall be in containers constructed of nonconductive material, maintained in good condition, and kept closed.

(e) Transportation of explosives or detonators in underground mines

Explosives or detonators shall be transported in special closed containers (1) in cars moved by means of a locomotive or rope, (2) on belts, (3) in shuttle cars, or (4) in equipment designed especially to transport such explosives or detonators.

(f) Storage of explosives and detonators in working sections of underground mines; containers; locations

When supplies of explosives and detonators for use in one or more working sections are stored underground, they shall be kept in section boxes or magazines of substantial construction with no metal exposed on the inside, located at least twenty-five feet from roadways and power wires, and in a dry, well rock-dusted location protected from falls of roof, except in pitching beds, where it is not possible to comply with the location requirement, such boxes shall be placed in niches cut into the solid coal or rock.

(g) Location of explosive and detonator containers in working places of underground mines

Explosives and detonators stored in the working places shall be kept in separate closed containers which shall be located out of the line of blast and not less than fifty feet from the working face and fifteen feet from any pipeline, powerline, rail, or conveyor, except that, if kept in niches in the rib, the distance from any pipeline, powerline, rail, or conveyor shall be at least five feet. Such explosives and detonators, when stored, shall be separated by a distance of at least five feet.

(Pub. L. 91-173, title III, §313, Dec. 30, 1969, 83 Stat. 785.)

Statutory Notes and Related Subsidiaries

EFFECTIVE DATE

Section operative 90 days after Dec. 30, 1969, except to the extent an earlier date is specifically provided for in Pub. L. 91-173, see section 509 of Pub. L. 91-173, set out as a note under section 801 of this title.

§ 874. Hoisting and mantrips

(a) Transporting of persons; required equipment and capabilities; safety catches; daily examinations; operators

Every hoist used to transport persons at a coal mine shall be equipped with overspeed,

overwind, and automatic stop controls. Every hoist handling platforms, cages, or other devices used to transport persons shall be equipped with brakes capable of stopping the fully loaded platform, cage, or other device; with hoisting cable adequately strong to sustain the fully loaded platform, cage, or other device; and have a proper margin of safety. Cages, platforms, or other devices which are used to transport persons in shafts and slopes shall be equipped with safety catches or other no less effective devices approved by the Secretary that act quickly and effectively in an emergency, and such catches shall be tested at least once every two months. Hoisting equipment, including automatic elevators, that is used to transport persons shall be examined daily. Where persons are transported into, or out of, a coal mine by hoists, a qualified hoisting engineer shall be on duty while any person is underground, except that no such engineer shall be required for automatically operated cages, platforms, or elevators.

(b) Promulgation of other safeguards

Other safeguards adequate, in the judgment of an authorized representative of the Secretary, to minimize hazards with respect to transportation of men and materials shall be provided.

(c) Rated capacities; indicator for position of cage

Hoists shall have rated capacities consistent with the loads handled and the recommended safety factors of the ropes used. An accurate and reliable indicator of the position of the cage, platform, skip, bucket, or cars shall be provided.

(d) Methods for signaling between shaft stations and hoist rooms

There shall be at least two effective methods approved by the Secretary of signaling between each of the shaft stations and the hoist room, one of which shall be a telephone or speaking tube.

(e) Braking equipment for haulage cars used in underground mines

Each locomotive and haulage car used in an underground coal mine shall be equipped with automatic brakes, where space permits. Where space does not permit automatic brakes, locomotives and haulage cars shall be subject to speed reduction gear, or other similar devices approved by the Secretary which are designed to stop the locomotives and haulage cars with the proper margin of safety.

(f) Automatic couplers for haulage equipment

All haulage equipment acquired by an operator of a coal mine on or after one year after the operative date of this subchapter shall be equipped with automatic couplers which couple by impact and uncouple without the necessity of persons going between the ends of such equipment. All haulage equipment without automatic couplers in use in a mine on the operative date of this subchapter shall also be so equipped within four years after the operative date of this subchapter.

(Pub. L. 91-173, title III, §314, Dec. 30, 1969, 83 Stat. 786.)

Editorial Notes

REFERENCES IN TEXT

For the operative date of this subchapter, referred to in subsec. (f), see section 509 of Pub. L. 91-173, set out as an Effective Date note under section 801 of this title.

Statutory Notes and Related Subsidiaries

EFFECTIVE DATE

Section operative 90 days after Dec. 30, 1969, except to the extent an earlier date is specifically provided for in Pub. L. 91-173, see section 509 of Pub. L. 91-173, set out as a note under section 801 of this title.

§ 875. Emergency shelters; construction; contents; implementation plans

The Secretary or an authorized representative of the Secretary may prescribe in any coal mine that rescue chambers, properly sealed and ventilated, be erected at suitable locations in the mine to which persons may go in case of an emergency for protection against hazards. Such chambers shall be properly equipped with first aid materials, an adequate supply of air and self-contained breathing equipment, an independent communication system to the surface, and proper accommodations for the persons while awaiting rescue, and such other equipment as the Secretary may require. A plan for the erection, maintenance, and revisions of such chambers and the training of the miners in their proper use shall be submitted by the operator to the Secretary for his approval.

(Pub. L. 91-173, title III, §315, Dec. 30, 1969, 83 Stat. 787.)

Editorial Notes

EFFECTIVE DATE

Section operative 90 days after Dec. 30, 1969, except to the extent an earlier date is specifically provided for in Pub. L. 91-173, see section 509 of Pub. L. 91-173, set out as a note under section 801 of this title.

Statutory Notes and Related Subsidiaries

REGULATIONS

Pub. L. 110-161, div. G, title I, §112(b), Dec. 26, 2007, 121 Stat. 2168, provided that: "Not later than June 15, 2008, the Secretary of Labor shall propose regulations pursuant to section 315 of the Federal Coal Mine Health and Safety Act of 1969 [30 U.S.C. 875], consistent with the recommendations of the National Institute for Occupational Safety and Health pursuant to section 13 of the MINER Act (Public Law 109-236) [120 Stat. 504], requiring rescue chambers, or facilities that afford at least the same measure of protection, in underground coal mines. The Secretary shall finalize the regulations not later than December 31, 2008."

§ 876. Communication facilities; locations and emergency response plans**(a) In general**

Telephone service or equivalent two-way communication facilities, approved by the Secretary or his authorized representative, shall be provided between the surface and each landing of main shafts and slopes and between the surface and each working section of any coal mine that is more than one hundred feet from a portal.

(b) Accident preparedness and response**(1) In general**

Each underground coal mine operator shall carry out on a continuing basis a program to improve accident preparedness and response at each mine.

(2) Response and preparedness plan**(A) In general**

Not later than 60 days after June 15, 2006, each underground coal mine operator shall develop and adopt a written accident response plan that complies with this subsection with respect to each mine of the operator, and periodically update such plans to reflect changes in operations in the mine, advances in technology, or other relevant considerations. Each such operator shall make the accident response plan available to the miners and the miners' representatives.

(B) Plan requirements

An accident response plan under subparagraph (A) shall—

- (i) provide for the evacuation of all individuals endangered by an emergency; and
- (ii) provide for the maintenance of individuals trapped underground in the event that miners are not able to evacuate the mine.

(C) Plan approval

The accident response plan under subparagraph (A) shall be subject to review and approval by the Secretary. In determining whether to approve a particular plan the Secretary shall take into consideration all comments submitted by miners or their representatives. Approved plans shall—

- (i) afford miners a level of safety protection at least consistent with the existing standards, including standards mandated by law and regulation;
- (ii) reflect the most recent credible scientific research;
- (iii) be technologically feasible, make use of current commercially available technology, and account for the specific physical characteristics of the mine; and
- (iv) reflect the improvements in mine safety gained from experience under this chapter and other worker safety and health laws.

(D) Plan review

The accident response plan under subparagraph (A) shall be reviewed periodically, but at least every 6 months, by the Secretary. In such periodic reviews, the Secretary shall consider all comments submitted by miners or miners' representatives and intervening advancements in science and technology that could be implemented to enhance miners' ability to evacuate or otherwise survive in an emergency.

(E) Plan content-general requirements

To be approved under subparagraph (C), an accident response plan shall include the following:

(i) Post-accident communications

The plan shall provide for a redundant means of communication with the surface